

SKS
WELDING SYSTEMS

WELD PACKAGE FRONT PULL 8

The **Weld Package** for your Welding Tasks
from the Power Source to the Contact Tip

WATER-COOLED



CONTENT

Power Source • Weld Process
Controller • Software •
Interface • Wire Feeder Unit •
Wire Guidance •
Cable Bundle • Control Cable •
Torch System • Torch Necks •
Consumables

WELDING PROCESSES

GMAW
Pulse
MIG-Brazing
microMIG
microMIG-cc




**ALU
MINUM**

SKS Weld Package: System design

The Frontpull 8 Weld Package contains:

- A Integrated solution: power source, weld process controller and interface in one device
- 1 Power Source
- 2 Weld Process Controller and Software/IT
- 3 Robot Interface
- 4 Frontpull Module
- 5 Wire Guidance
- 6 Ground Cable
- 7 Control Cable
- 8 Cable Bundle
- 9 Torch System Frontpull 8
- 10 Torch Neck/Consumables
- 11 Water Cooling
- 12 Reamer Blades
- 13 TCP Dimensions/Checking Fixtures/
Torch Cleaning Stations



For installations with outer cable dress.


This brochure contains information about the SKS Weld Package, the torch system Frontpull 8, as well as consumables and spare parts. There are various features of the welding machine components and torch systems available depending on the robot system and the welding task.

The **Frontpull 8 Weld Package** can be used with all common industrial robots.

A



Components **1**, **2** & **3**
also available as an integrated
solution – LSQ COMPACT.



Frontpull 8 – water-cooled for aluminum applications

Processes:	microMIG, microMIG-cc, KF-pulse, Puls, MIG brazing, GMAW
Wire materials:	aluminum
Compatibility:	for all common industrial robots
Weight:	2.5 kg
Max. power:	420 A – 60 % duty cycle/40 °C, water-cooled
Wire diameter:	1.2 mm and 1.6 mm
TCP accuracy:	± 0.2 (400 mm)

LSQ COMPACT



The LSQ COMPACT IoT was designed as an integrated welding system, combining the weld process controller, Fieldbus interface, and power supply into one unit, resulting in a compact size with fewer external connections – for easy installation. Even with its compact size and integrated design, this machine is powerful and incorporates 35 years of technological knowledge. Whether you are welding thick aluminum plates or thin stainless steel, a process is available to support your specific needs. All processes are unlocked and readily available. You do not need an additional license or passcode to use them.

Up Front Pricing:

**No hidden costs for
welding processes
and software functions.**

A Integrated Solution LSQ COMPACT

Compact: All in One, All Inclusive. Compatible with
SKS Weld Packages: Power Clutch, Power Joint and Frontpull.

**READY FOR
GLOBAL USE**
CE, UL & CCC
CERTIFIED

**MQTT
OPC UA****
+ TRACEABILITY



POWER SOURCE
+ PROCESS CONTROLLER
+ ROBOT INTERFACE

MATERIALS:

steel
low- & high-alloy steel
copper alloys
galvanized steel
aluminum*



**FREE WELD DATA
DOCUMENTATION
& MANAGEMENT**

420 A
60% DUTY CYCLE
AT 40°C

INCLUDES THE WELDING PROCESSES AND FUNCTIONS:

GMAW
I-pulse
KF-pulse
microMIG*
microMIG-cc*
MMT-x*
DP-Fast
MIG-Brazing
Synchroweld
AutoComp

* Only in combination with Frontpull torch system. Further information can be found in the Frontpull Weld Package
** Only available in LSQ COMPACT IoT

A Integrated Solution LSQ COMPACT



LSQ3 COMPACT Lite



LSQ5 COMPACT IoT

Integrated power source

The LSQ COMPACT Lite and IoT are available with LSQ 3 and LSQ 5 power sources to provide the best solution for your application. The technical data can be found on the following pages.

Integrated weld process controller

While the LSQ COMPACT Lite is designed for maximum cost efficiency, the LSQ COMPACT IoT offers additional features such as the Internet of Things (IoT), MQTT, and OPC UA support. This advanced weld process controller enables extended real-time monitoring and analysis of welding processes, resulting in improved quality assurance and more precise control of the process.

Specifications	Lite	IoT
Operation via	buttons	touch screen
Programs	15.872	15.872
Ports	USB, SD card slot	Ethernet, SD card slot
MQTT / OPC UA	No	Yes
Remote Control	Q8Tool	Q8Tool, VNC client

Integrated interface

With the included Fieldbus Interface FB5 the system can be perfectly integrated into existing Fieldbus environments. Various Fieldbus types are available e.g. EtherNet/IP, Profinet CU.

Overview LSQ COMPACT	Part-No.
LSQ5 COMPACT Lite	77-1185-71x
LSQ3 COMPACT Lite	77-1184-78x
LSQ5 COMPACT IoT	77-1185-77x
LSQ3 COMPACT IoT	77-1184-81x
LSQ5 CCC COMPACT Lite	77-1185-73x
LSQ3 CCC COMPACT Lite	77-1184-73x
LSQ5 CCC COMPACT IoT	77-1185-79x
LSQ3 CCC COMPACT IoT	77-1184-79x

Please note:

Various field bus types available. Please enter the number you require in place of the x:
1 = EtherNet/IP | 2 = Profinet CU | 3 = EtherCAT



Accessories: Wall mount for LSQ5

Space-saving design that makes for easy cleaning/maintenance.

Wall mount

Overview of wall mounts	Part-No.
Wall mount for power source LSQ5 and LSQ5 COMPACT	77-1180-01
Wall mount for power source LSQ3 and LSQ3 COMPACT	integrated

1 Power source



LSQ5 power source

LSQ5 power source with Direct Control Technology (DCT)

The LSQ5 ensures the optimum arc energy. It uniquely adjusts to different weld processes. Unlike conventional power sources with inverter technology, the LSQ5 with Direct Control Technology controls its switching transistors without any fixed clock frequency according to the needs of the weld process. Without any delay, the energy needed for the process is provided instantly. The flexible fine tuning is done by a central processor. The CPU continuously analyzes the weld process and current/voltage values on the basis of data obtained and optimally drives the switching transistors of the power section. This results in an extremely high efficiency and a low temperature development.

The power source can be configured with only two buttons and four LED indicators. For worldwide usage, voltages can be configured without opening the power source.



LSQ3 power source

LSQ3 power source with Direct Control Technology (DCT)

The LSQ3 offers enough power reserves for special weld tasks like chassis and exhaust parts and other thin sheet metal applications.

Overview of power sources	Part-No.
DCT power source LSQ5 Direct-Control-Technology	77-1185-00
DCT power source LSQ3 Direct-Control-Technology	77-1184-50
DCT power source LSQ5-CCC Direct-Control-Technology	77-1185-60
DCT power source LSQ3-CCC Direct-Control-Technology	77-1184-40

The main benefits are:

- DCT provides a speed regulation up to ten times higher compared to conventional inverter technology. This leads to excellent control behavior and shorter response times.
- The weld properties are substantially improved. Software replaces hardware: Fewer components also increase the reliability in continuous operation.

Specifications	LSQ5 (-CCC)	LSQ3 (-CCC)
Performance	420 A - 60% duty cycle/40 °C (400 A)	340 A - 60% duty cycle/40 °C
Processes and functions	GMAW, I-pulse, KF-pulse, microMIG*, microMIG-cc*, MMT-x*, DP-Fast, MIG-Brazing, Synchronweld, AutoComp	
Weight	49 kg	37 kg
Primary voltage	3 x 400 (480) V	
Wall mounting	Yes (optional)	Yes (integrated)
Conformities	CE, CSA, UL (CCC)	CE (CCC)
Dimensions	450 x 400 x 540 mm	450 x 330 x 540 mm

* Only in combination with Frontpull torch system. Further information can be found in the Frontpull Weld Package.

2 Weld process controller

Innovative Control Concepts with Touch Screen.


With the new Q84r and the compact Q84s up to four weld machines can be controlled centrally.

- **Parameter settings** completely integrated in the SKS software
- **Documentation** of measurements + TCP speed

- ✓ All settings on a single screen
- ✓ All measurements on a single screen
- ✓ All SKS welding processes and functions available
- ✓ Ready to use Industry 4.0 protocols (MQTT + OPC UA) and data traceability!



2 Weld process controller



Controlling up to four weld machines at the same time

The new Q84r and Q84s are equipped with a touch screen, an innovative usability concept and an advanced visualization technology for much easier operating. The user interfaces have the look and feel of the Q8Tool4 software. Individual weld process controllers are in card slots in the Q84r/s. This new weld process controller concept can host up to four weld process controller cards. Each card independently controls a weld machine. As an alternative to the Q84r/s weld process controllers, the Q80 has been developed to control a single weld machine.

2 Weld process controller



Q84r weld process controller



Q84r Weld process controller

Please note:

The Q84r/s can be equipped with up to four weld process controller cards.

Weld process controller Q84r/s

The universal weld process controllers Q84r and Q84s calculate the optimal parameters for each welding process. Only basic data such as material, wire type, wire feed speed and type of gas must be entered. The Q84r is equipped with a 10" touch screen, the space-saving Q84s with a 7" touch screen. For wall mounting the display of the Q84s can be rotated by an angle of 180°.

- Processes and functions: GMAW, I-pulse, KF-pulse, microMIG*, microMIG-cc*, MMT-x*, DP-Fast, MIG Brazing, Synchroweld, AutoComp
- Programs: 15.872 (x4)
- General functions: Display and saving of readings, alarms
- Monitoring functions: Weld current monitoring, auto compensation, arc and ignition monitoring, motor current, gas and water monitoring
- Easy to network via Ethernet: Traceability
- Ports: RJ45-Ethernet, SPW-Bus, SD card slot
- Remote Control/Administration: Q8Tool, VNC client
- Supports MQTT / OPC UA

Overview weld process controllers	Part-No.(Q84s)	Part-No. (Q84r)
Q84s/r weld process controller with one weld card	77-7410-001	77-7310-001
Q84s/r weld process controller with two weld cards	77-7420-001	77-7320-001
Q84s/r weld process controller with three weld cards	77-7430-001	77-7330-001
Q84s/r weld process controller with four weld cards	77-7440-001	77-7340-001

Overview Q84r/s mounting kits	Part-No.
Bracket for Q84r for mounting onto power source LSQ3/5	77-7240-01
Mounting brackets for Q80/Q84s for mounting onto power source LSQ3/5	77-7240-06
Bracket for Q84r for wall mounting	77-7240-02
Bracket for Q84r mounting in the robot cabinet	77-7240-05

Overview Q84r/s accessories	Part-No.
Connection cable for Q84r/s 5m with open end (optional)	77-3305-00
Plug for external power supply of Q84r/s	77-7240-96
USB adapter for SD/microSD cards	91-8-1

Overview Q84r/s replacement parts	Part-No.
Touchpen for Q80 / Q84r/s weld process controller (spare part)	77-7240-03
SDHC card 8GB for Q84r/Q84s/Q80 weld process controllers	91-8-6

* Only in combination with Frontpull torch system. Further information can be found in the Frontpull Weld Package.

2 Weld process controller



Q80 weld process controller – front view



Q80 weld process controller – back view



Weld process controller Q80

The Q80 is the alternative to the Q84r/s. It has the same functionality/features as a single weld card of the Q84r/s - optimized for a single weld machine. With the universal Q80 all parameters and values needed for the weld task can be optimally calculated

- Processes/functions/general functions see Q84r/s
- Easy to network via Ethernet: up to traceability
- Ports: RJ45-Ethernet, SPW-Bus, SD card slot
- Wall mounting capability
- Remote Control / Administration: Q8Tool
- Supports MQTT / OPC UA

Overview weld process controller	Part-No.
Q80 weld process controller	77-7260-001
Overview Q80 mounting kits	Part-No.
Bracket for mounting onto power source LSQ5	77-7240-06
Overview Q80 accessories	Part-No.
USB adapter for SD-/microSD card	91-8-1
Overview Q80 replacement parts	Part-No.
Touchpen for Q80 / Q84r/s weld process controller (replacement part)	77-7240-03
SDHC card 8GB for Q84r/Q84s/Q80 weld process controllers	91-8-6

2 Software/IT



Q8Tool software

The Q8Tool software provides accurate and comprehensive process monitoring. The user can store weld parameters for documentation on a PC and/or administrate them. It offers basic functions such as reading, modifying and documenting of weld parameters. Additionally, new weld parameters can be created and transferred to the universal weld process controllers. The weld data is portable and the installation of further control units on new equipment is easy. Also, the software allows reading and exporting of measurements and alarms. Graphical and numerical recording of measures helps defining and optimizing parameters for new parts. Users have a powerful tool for analyzing and documenting their weld results.

Network

The weld process controller units can easily be networked via Ethernet ports: Time savings through centralized administration of all controllers within the corporate network. There is a central backup of all welding parameters, management of user rights and access, process monitoring up to traceability. The Q8Tool software is provided free of charge with the weld process controller. No additional hardware or software is required.

3 Robot interface

Perfect integration.

Interfacing all industrial robot types.



By the use of Fieldbus Interface FB5 the system can be perfectly integrated into existing Fieldbus environments. For analog and digital environments the universal interface UNI5 is available on request.

Standard application

Fieldbus systems exchange signals via serial communication. The Fieldbus master, usually the robot controller or overall system controller, bundles and processes the signals of the connected Fieldbus, including the welding machine. Standard Fieldbus systems are e.g., Interbus-S, Profibus DP or DeviceNet.

The Fieldbus interface FB5 translates the Fieldbus signals for the welding machine using a standardized protocol. It makes no difference which type of Fieldbus system is used. The signals are always at the same place on the Fieldbus. This makes the preparation of the robot or system controller much easier.

3 Robot interface



FB5 Fieldbus Interface: mounting onto the power source



FB5 Fieldbus Interface: mounting onto the cabinet

Fieldbus application

Various Fieldbus types are supported (e.g. Profibus DP, DeviceNet). The Fieldbus interface has drilled bore holes for flexible mounting within the weld cell. Two additional mounting kits provide easy installation at the power source or into the cabinet. Additionally, external power can be connected to the interface. More details on solutions for the specific Fieldbus types are available on request.

Overview FB5 interfaces	Part-No.
Fieldbus interface FB5 Interbus-S (copper line)	77-3-1
Fieldbus interface FB5 Profibus DP	77-3-2
Fieldbus interface FB5 DeviceNet	77-3-3
Fieldbus interface FB5 EtherCAT	77-3-4
Fieldbus interface FB5 Profinet IRT (copper line)	77-3-5
Fieldbus interface FB5 Profinet IRT (LWL 2 Port)	77-3-6
Fieldbus interface FB5 Interbus-S (LWL FSMA)	77-3-7
Fieldbus interface FB5 Ethernet/IP	77-3-8

Cabinet mounting	Part-No.
Mounting kit for cabinet	77-1182-02
Cabinet cable 2m FB5 with device plug and cable socket	77-3102-02

Power source mounting	Part-No.
Bracket for FB5/Q6pw for mounting onto LSQ3/5	77-1182-03

Optional power supply (24V)	Part-No.
Connection cable 2.0 m (with open end)	77-1182-04

SYNCHROWELD

Synchroweld unites the weld system and robot by a communication protocol (RWDE). This technology allows the weld system to get the actual robot speed and automatically adjusts the weld parameters and laser power within defined limits. The result is a constant energy per unit length. At the same time, the programming effort can be significantly reduced.

Please note:

Further information on Synchroweld with ABB, Fanuc, KUKA, Yaskawa can be found in our Synchroweld brochure.

4 Frontpull Module

Frontpull 8 Module

Modular standard.

The Frontpull module uses the proven industrial strength housing of the PF6 wire feeder. The installation is easy because the wire feeder brackets also fit the Frontpull module.




Frontpull 8 Module with integrated gas flow sensor

The motor control board is included in the module. The wire feeder mechanics are located in the torch. This separation protects the electronics from the noise of the welding process. The PF6 proven power pin block connection technology is also used in the Frontpull module to reach the most possible standardization.

The Frontpull module is available with an additional monitoring functionality: an integrated gas-flow-sensor. The weld process controller displays the gas flow values, and can also be triggered to an alarm, in case of a non-defined gas flow rate.

Overview of Frontpull 8 Module	Part-No.
FPM8 Frontpull 8 Module with integrated gas flow sensor	10-15-300
Shielding Gas Saver ECO GS40 ¼", adjustable	93-62-5



Center guide

The center guide ensures a defined routing of the welding wire within the four roll drive.

Overview center guide	Part-No.
Center guide for PF5/6 wire feeder, aluminum wire-ø up to 1.6mm	12-2-1-19

4 Frontpull Module



Please note:

Two drive rolls per system are needed.

Please note:

Drive rolls for wires in inch sizes available on request.

Drive roll

For wire diameters 1.2 mm and 1.6 mm (U-groove for aluminum applications)

Overview of drive rolls	Part-No.
Wire- \varnothing 1.2 mm, V-groove	12-2-4-112
Wire- \varnothing 1.6 mm, V-groove	12-2-4-116



Please note:

Two pressure rolls, two locating bolts and two knurled screws are needed per system.

Pressure roll

The pressure roll ensures a defined pressure of the welding wire into the specific groove shape of the drive roll.

Overview of pressure rolls	Part-No.
Pressure roll for aluminum applications with U-groove 1.2mm	12-2-5-112
Pressure roll for aluminum applications with U-groove 1.6mm	12-2-5-116
Locating bolt for pressure roll U-groove	12-2-1-23
Knurled screw for pressure roll U-groove	12-2-1-24



Please note:

Wire feeder brackets for further robot types are available on request.

Wire feeder bracket

Wire feeder bracket with holes and mounting material for quick and easy installation.

Overview of wire feeder brackets	Part-No.
For robot type-ABB (single wire)	
IRB 2400-10/1.55	14-2-4
IRB 2600-12/1.85	14-2-7
For robot type-FANUC (single wire) aht	
AM 100iD / AM 120iD / M-10iD/8L / M-20iD/12L	14-4-2


For robot type-KUKA (single wire)

KR 8 R1620 / KR 10 R1420 / KR 12 R1810 **14-3-2**

For robot type-YASKAWA (single wire)

AR 1440 / GP 12 **14-1-26**
AR 2010 **14-1-16**

5 Polymer „L“ Push wire guidance



Polymer wire guidance

Please note:

Furhter information can be found in our brochure "Wire guidance" (DOC-0193EN).

With the new SKS polymer guidance, the high efficiency of the whole system extends up to the drum.

Advantages of polymer wire guidance:

- Extraordinary good glide properties reduces motor load
- Minimized abrasive wear and reduced dirt in wire feeder and torch system
- Lightweight design and a high inherent stability for easy installation
- Length can be freely chosen by the customer
- Cost optimized exchange: only the polymer conduit must be changed, connectors are reuseable.
- Optimized materials for longer life and reduced downtimes

Overview of polymer wire guidances


	Part-No.
Wire inlet body for PF5/6 IG G1/4" / polymer conduit	10-2-0-63
Polymer wire guidance, per meter, version L, blue	44-9-1
Wire drum connection with quick connector	44-40-9

Option

Overview of strain-relief on wire guidance

	Part-No.
Strain-relief wire guidance for PF5/6	14-10-6

5 Rolliner 3G wire guidance



- 1 Wire inlet body for PF5/6 with inner thread
- 2 Connection set Rolliner NG
- 3 Connector wire outlet
- 4 Wire Guidance Rolliner 3G in corrugated tube black NW23
- 5 Connector wire inlet
- 6 Wire drum connector for Rolliner

Rolliner 3G Wire guidance is suitable for all applications where higher wire feeding requirements are needed.

Benefits:

- Optimized sliding properties with roller-supported wire guidance
- High flexibility due to segmentation of roller parts
- Suitable for use in harsh environments
- Universally application (steel, stainless steel, filler wire, aluminum)

Overview of Rolliner 3G wire guidance	Part-No.
Wire inlet body for PF5/6 with $\frac{1}{4}$ " NPTF inner thread	10-2-0-60
Connection set Rolliner NG for drum or wire feeder	44-60-21
Connector wire outlet for Rolliner 3G	44-60-42
Mounting clip for Rolliner 3G	44-60-45
Wire Guidance Rolliner 3G per meter	44-60-40
Corrugated tube PUR black NW23 per meter	91-3-2
Connector wire inlet for Rolliner 3G	44-60-41
Wire drum connector for Rolliner NG	44-60-30

Option

Overview of strain-relief on wire guidance	Part-No.
Strain-relief wire guidance for Rolliner	14-10-8
Clamping Piece Rolliner 3G on Cable Bundle -A-	44-60-48

Please note:

Two connection sets are needed.

Alternative



Wire inlet bodies for additional systems

Beside the wire inlet body for the SKS wire guidance, inlet bodies for additional systems are available.

Overview of wire inlet bodies for additional systems	Part-No.
Wire inlet body for PF5/6 with M10 internal thread for ESAB	10-2-0-50
Wire inlet body for PF5/6 with 9.6 mm bore hole	10-2-0-52
Wire inlet body for PF5/6 with 13 mm bore hole	10-2-0-53
Wire inlet body for PF5/6 with PG9 thread	10-2-0-56
Wire inlet body for PF5/6 with internal thread $\frac{1}{4}$ " NPTF	10-2-0-60
Overview of wire inlet bodies for aluminum wire	Part-No.
for type 50/52/53/60/61	10-2-0-57-3
for type 56	10-2-0-58-3

6 Ground cable



Please note:

Further lengths and diameters available on request

Ground cable with 70 mm² connector and cable plug

The use of highly pure copper reduces the electric resistance supporting the welding process. Manufactured as of DIN VDE 0285-525-2-81 / DIN EN 50525-2-81.

Overview of ground cables	Part-No.
Ground cable 70 mm ² 6 m with DIX plug and cable lug	228078106
Ground cable 70 mm ² 10 m with DIX plug and cable lug	228078100

Option

Overview of ground cables	Part-No.
Ground cable 95 mm ² 6 m with DIX plug and cable lug	228080106
Ground cable 95 mm ² 10 m with DIX plug and cable lug	228080110

7 Control cable



Please note:

For the Frontpull 8 system three control cables are needed. One control cable is already included in the cable bundle.

Please note:

Further lengths available on request.

Control cable: L700/SPW-Bus

One cable to connect power source, weld process controller, interface and frontpull module. By use of one cable stock and installation is simplified. The power is supplied via this cable. An external supply is not necessary.

Overview of control cables	Part-No.
Control cable 0.5m L700/SPW-Bus	541031050
Control cable 1m L700/SPW-Bus	541031001
Control cable 2m L700/SPW-Bus	541031002
Control cable 3m L700/SPW-Bus	541031003
Control cable 5m L700/SPW-Bus	541031005
Control cable 7m L700/SPW-Bus	541031007
Control cable 10m L700/SPW-Bus	541031000
Control cable 12m L700/SPW-Bus	541031012
Control cable 15m L700/SPW-Bus	541031015

Plug & Play: Control cable L700

The advantages of a system concept are revealed by its details: One standard control cable (L700) connects all system components (power source, robot interface, weld process controller and Frontpull module) within the welding system.

The system is expandable: Other components can be integrated at any time into an existing system. New devices are automatically detected.



Power Source



Robot Interface



Weld Process Controller



Frontpull Module

8 Cable bundles



Cable bundles: Power source to Frontpull Module

Coaxial power cable 72 mm² with internal gas flow, control cable L700. disconnect cable, corrugated tube and cable holder. Air-cooled versi

Overview of cable bundles	Part-No.
Cable bundle 72mm ² 5m -W- LSQ-PF5/6	20-8-5
Cable bundle 72mm ² 7m -W- LSQ-PF5/6	20-8-7
Cable bundle 72mm ² 10m -W- LSQ-PF5/6	20-8-10


Alternative

Overview of cable bundles with air-blast function	Part-No.
Cable bundle 72mm ² 5m -LW- LSQ-PF5/6 with air-blast function	20-23-5
Cable bundle 72mm ² 7m -W- LSQ-PF5/6 with air-blast function	20-23-7
Cable bundle 72mm ² 10m -W- LSQ-PF5/6 with air-blast function	20-23-10
Air blast valve for mounting onto the wire feeder bracket	93-50

Please note:

Further lengths available on request.

8 Cable bundles: Clamping set



Mounting cable bundle: clamping set -W-

Provides perfect installation of the cable bundle for all different robot types. Undesired cable movements are prevented. This results in higher lifetime.

Overview of clamping sets	Part-No.	
For robot type-ABB		For robot type-KUKA
IRB 2400-10/1.55	not available	KR 8 R1620 / KR 10 R1420 91-3-0-61-17
IRB 2600-12/1.85	91-3-0-61-11	KR 12 R1810 91-3-0-61-12
For robot type-FANUC		For robot type-YASKAWA
AM 100iD / AM 120iD	91-3-0-61-23 (optional 91-3-0-61-30)	AR 1440 / AR 2010 / GP 12 91-3-0-61-22
M-10iD/8L / M-20iD/12L	91-3-0-61-23 (optional 91-3-0-61-30)	

Please note:

Clamping sets for further robot types are available on request.

Alternative

Mounting for WF-bracket	Part-No.
Mounting for WF-bracket for external guided cable bundle	14-10-10


8 Dividable cable bundles

Alternative



70 mm² Connection from power source to connection bracket -W-

Length	Part-No.	Part-No. (with air-blast function)
5 m	20-18-5	20-28-5
7 m	20-18-7	20-28-7
10 m	20-18-10	20-28-10



Connection bracket for cable bundles (PF5/6) -W-

	Part-No.
Verbindungskonsole	20-17-0-3



Connection 72 mm² from connection bracket to PF5/6 -W-

Length	Part-No.	Part-No. (with air-blast function)
3 m	20-17-3	20-24-3
5 m	20-17-5	20-24-5
7 m	20-17-7	20-24-7

Please note:


Further lengths available on request.

Please note:

For use of the air blast function the air blast valve (Part-No. 93-50) is required.

Cable bundle with separation between power source and wire feeder PF5/6


The moving parts of the cable bundle (next to the robot) are separated from the non-moving parts (power source). In case of maintenance work, only the moving parts have to be changed. The quick and easy replacement concept results in time and cost savings.



9 Torch system Frontpull 8

Welding evolution: Spatter-free ignition.

The Frontpull 8 torch system.



The latest innovation from SKS is the new Frontpull 8 torch system, in which wire feeder and torch system are merged into a single unit. The result: support of spatter-free ignition, high feeding precision close to the welding process and almost spatter-free welding joints – particularly with soft aluminum wires, as well as a high level of reliability through the use of standardized motor technology.

Frontpull 8 – water-cooled for aluminum applications

Processes:	microMIG, microMIG-cc, KF-pulse, Puls, MIG brazing, GMAW
Wire materials:	aluminum
Compatibility:	for all common industrial robots
Weight:	2.5 kg
Max. power:	420 A – 60 % duty cycle/40 °C, water-cooled
Wire diameter:	1.2 mm and 1.6 mm
TCP accuracy:	± 0.2 (400 mm)

9 Torch system Frontpull 8: Parts overview

All parts of the Frontpull 8 torch system at a glance.



- 9a Collision Protection
- 9b Torch Body and Mounting Arm
- 9c Accessories Torch Body
- 9d Robot Mounting
- 9e Torch Cable and Accessories
- 10a Torch Neck
- 10b Consumables
- 10c Gas Nozzle
- 11 Water Cooling

9 Torch system Frontpull 8: Parts overview



9a Torch system: Collision protection



Collision protection Power Clutch HD for welding robots with outer cable dress

The SKS collision protection is based on the Power Joint concept, continuing the modular structure of the SKS components. This ensures the same high precision TCP accuracy in the Frontpull 8 as found in SKS Power Joint systems. Aside from the industrial proven Power Clutch, an adaptor without collision protection is available. This adaptor has the same component length to maintain modularity and compliance with the TCP.

Power Clutch 2 HD	Part-No.
SKS collision protection Power Clutch 2 Heavy Duty	71-16
Solid Mount for SKS torch systems	93-33

Technical data Power Clutch 2 HD	
Collision protection	deflection 10°
Reset accuracy	± 0.2 mm with TCP 400 mm
Weight	1.5 kg

9b Torch system: Torch body and mounting arm



Frontpull 8 torch system including mounting arm


With a weight of only 2.5 kilograms, the Frontpull 8 torch supports the new generation of robots. The requirement for a fast acceleration and high response speeds are implemented. A wire feeding support unit has been placed in an external box to save weight at the foremost robot axis. The Frontpull 8 torch provides the most accurate wire feeding closest to the process. The "Lift-Arc" spatter-free ignition routine and a spatter reduced welding process provide an additional quality improvement. With the microMIG/microMIG-cc Technology (MMT) the Frontpull 8 torch provides heat-reduced welding, virtually spatter-free.

Frontpull 8	Part-No.
Frontpull 8 with torch body and mounting arm (23° version)	10-15
Frontpull 8 with torch body and mounting arm (0° version)	10-16


Advantages:

- Standard components (power source, weld process controller)
- Standard SKS torches and consumables can be used
- The wire feeder is at the sixth robot axis providing for a highly precise wire feeding
- The Frontpull 8 torch system is based on the proven SKS Power Joint and Power Feeder design
- Supports spatter-free ignition
- High reliability – No synchronization problems

Technical data	
Weight	ca. 2.5 kg
Wire feeding speed	0 - 25 m/min



Frontpull 8 (0° version)



Frontpull 8 (23° version)

9c Torch system: Accessories torch body



Please note:

One drive roll per system is needed.



Please note:

One pressure roll, one locating bolt and one knurled screw are needed per system.

Drive roll

For wire diameters 1.2 mm and 1.6 mm (U-groove for aluminum applications)

Overview of drive rolls	Part-No.
Wire- \varnothing 1.2 mm, U-groove	12-2-4-112
Wire- \varnothing 1.6 mm, U-groove	12-2-4-116

Please note:


Drive rolls for wires in inch sizes available on request.

Pressure roll

The pressure roll ensures a defined pressure of the welding wire into the specific groove shape of the drive roll.

Overview of pressure rolls	Part-No.
Pressure roll for aluminum applications with U-groove 1.2mm	12-2-5-112
Pressure roll for aluminum applications with U-groove 1.6mm	12-2-5-116
Locating bolt pressure roll U-groove	12-2-1-23
Knurled screw for pressure roll U-groove	12-2-1-24

9d Torch system: Robot mounting



Please note:

Connection flanges for further cobots are available on request.

Connection flange Power Clutch

Overview of connection flanges	Part-No.	Insulation flange (when using 93-33)
For robot type-ABB		Part-No.
IRB 2400-10/1.55 / IRB 2600-12/1.85	63-4-5	63-2-5
For robot type-FANUC		
AM 100iD / AM 120iD / M-10iD/8L / M-20iD/12L	63-4-24	63-2-24
For robot type-KUKA		
KR 8 R1620 / KR 10 R1420	63-4-16	63-2-16
KR 12 R1810	63-4-3	63-2-3
For robot type-YASKAWA		
AR 1440 / AR 2010 / GP 12	63-4-8	63-2-8

TCP extension

The TCP-extension increases the freedom of accessibility and depth of immersion into the weld part/fixture.

Overview of TCP extensions	Part-No.
TCP extension 35 mm (for 0° version)	93-57



9e Torch system: Torch cable and accessories



Torch cable, outer cable dress for Frontpull 8 torch system

High flexible coaxial cable 72 mm² with Power Pin and torch connector.

Overview of recommended torch cable lengths for robots	Part-No.
for robot type-ABB	
IRB 2400-10/1.55	61-5-09
IRB 2600-12/1.85	61-5-10
for robot type-FANUC	
AM 100iD	61-5-09
AM 120iD	61-5-10
M-10iD/8L	61-5-12
M-20iD/12L	61-5-15

for robot type-KUKA

KR 8 R1620 / KR 10 R1420	61-5-09
KR 12 R1810	61-5-11

for robot type-YASKAWA

AR 1440 / GP 12	61-5-10
AR 2010	61-5-12

Overview of torch cables	Part-No.
0.75 m	61-5-075
0.9 m	61-5-09
1.0 m	61-5-10
1.1 m	61-5-11
1.2 m	61-5-12

1.5 m	61-5-15
1.8 m	61-5-18
2.0 m	61-5-20
2.4 m	61-5-24



Control cable for Frontpull 8 torch system

Connection between Frontpull 8 torch and Frontpull module

Overview of control cables	
Length	Part-No.
1.2 m	77-2013-06
1.5 m	77-2013-061
1.7 m	77-2013-063
1.8 m	77-2013-064
1.9 m	77-2013-065
2.0 m	77-2013-066
2.3 m	77-2013-062

2.6 m	77-2013-067
2.8 m	77-2013-068
3.2 m	77-2013-069

Velcro® tape for mounting (10 pcs.)	571040310
-------------------------------------	------------------

Please note:

Connection cable length = torch cable length + 0.8 m



Frontpull liner for aluminum wire

For the following wire diameters:

Wire-ø 1.2 and 1.6 mm

Overview of liners	Part-No.
Liner for aluminum wire-ø 1.2-1.6mm (per meter)	91-68-47025-25E
Clamp sleeve for aluminum liner (black)	44-30-7
Inset for Frontpull aluminum liner	44-30-14
Cap for Power Pin type M 20° for aluminum liner	61-2-0-2-7



Wire guidance for torch neck

Overview of liners	Part-No.
Frontpull liner for aluminum wire 1.0-1.6mm, ceramic-end	58-4-12-500
Inset for FP8i-L/FP8 Aluminum liner	44-30-14



Torch necks for Frontpull 8


SKS torch necks are available in different geometries and for a wide range of applications. With its innovative bayonet lock system, the SKS torch neck can be replaced quickly. This unique tool-free quick change system is also highly precise with TCP accuracy of $\pm 0,2$ mm.

Overview of torch necks			Application recommendations			
Type	Part-No.	angle [°]	Frontpull 8 – 23° version		Frontpull 8 – 0° version	
HQX dressing water-cooled	58-127-722-350-1	22	527.1	✓ ✓	570.77	✓
	58-127-722-400-1	22	573.1	✓	620.77	✓
	58-127-735-400-1	35	561.7	✓	619.69	✓
	58-127-745-350-1	45	506.2	✗	568.57	✓
	58-127-745-400-1	45	552.2	✗	618.57	✓
	58-427-7345-450-1	45	529.9	✗	607.07	✓ ✓
	58-427-7345-567-1	45	637.6	✗	724.07	✓

- ✓ ✓ Recommended standard torch neck
- ✓ Recommended
- ✗ Not recommended

Please note:

For information about steel applications please see our brochures "Frontpull 8 Steel".



Torch neck change with the SKS bayonet locking concept

Find an interactive animation of how it works in the QR code



Please note:

Animation using the example of a standard torch neck in the Power Joint Weld Package.



Power Lock Plus: retaining head

High performance retaining head optimized for aluminum applications

Overview of retaining heads	Part-No.
High performance HQX Power Lock Plus – aluminum application	43-20-11



Gas diffuser HQX for Power Lock Plus

Overview gas diffuser HQX	Part-No.
Gas diffuser HQX for aluminum application HD	43-27-8



Power Lock Plus: contact tip

- Tapered design for high TCP reproducibility
- Improved heat transfer extends lifetime
- Improved power transition: constant arc quality

Overview of contact tips	Part-No.
Contact tip Power Lock Plus aluminum wire Ø 1.2mm HD-CuCrZr	40-6-7-1.2AL
Contact tip Power Lock Plus aluminum wire Ø 1.6mm HD-CuCrZr	40-6-7-1.6AL

Please note:

Contact tips for wires in inch sizes available on request.

Please note:

An overview with dimensions can be found on the page after next.



Gas nozzles with thread

Overview of gas nozzles	Part-No.
16 mm	
flush, tapered	41-17-16-TF
long, tapered	41-17-16-TR



Tools and accessories

For replacement of contact tips: Fast exchange of contact tip without removing the gas nozzle

Overview of tools and accessories	Part-No.
Mounting tool SW7 for contact tip (Power Lock Plus)	51-9002-00
Stopper-Key for drive rolls (Std & Lite)	93-100-3-3
SKS Multitool for single wire torch systems	47-11
Tool box for aluminum applications	93-100-9-4



Programming tips

Programming tips for precise seam programming

Overview of programming tips	Part-No.
Stickout	
15 mm (Power Lock Plus)	65-11
15 mm (Power Lock Plus)	65-12

Hinweis:


An overview with dimensions can be found on the next page.

Hinweis:

Further information can be found in our brochure "Consumables" (DOC-0135EN).

10c

Gas nozzles: Overview dimensions



Please note:

Further gas nozzles, reamer blades and torch necks can be found in our consumables brochure.

Please note:

Dimensions in mm.

11 Water cooling



Water cooling

The water-cooled Frontpull 8 torch system has a cooling circuit for highest efficiency. The circuit is used for the direct cooling of the consumables. So the reflected energy of the welded parts can be dissipated directly from the consumables.

Water cooler UK500

With one cooling-circuit and passive cooling this water cooler provides best cooling directly at the process. Tank capacity 7 L.

Water cooler UK500	Part-No.
Water cooler UK500	541018200

Water cooler eChilly

The water cooler eChilly is active cooled and has two separated cooling circuits and provides best possible cooling efficiency next to the process. Up to two torch systems can be cooled independantly at the same time. Tank capacity 6.4 L.


Overview water cooler eChilly	Part-No.
Water cooler eChilly 1-special (active, two circuits)	541018400



Water cooling conduit for cooling jacket

Conduit for cooling jacket to dissipate heat from the consumables.

Overview water cooling conduit for cooling jacket	Part-No.
Water Lines Flow & Return conn. Torch to Water Module	71-8-23
Velcro® strip set (10 pcs. à 20cm)	571040310



Water monitoring

By monitoring the flow speed the heat transport from the frontend is ensured. Exceeding the limit triggers an according alarm.

Overview water monitoring	Part-No.
Water monitoring for Wire Feeder PF5/6-Series	93-11
Mounting for water module on Wire Feeder Bracket	93-11-5




Water filter

Cooling fluid may be contaminated with small particles, affecting the cooling efficiency. The water filter filters these particles out of the cooling fluid.

Overview water filter	Part-No.
Water filter with inset	93-11-6
Inset (replacement part)	91-60-F1060691350
Glysantin G40, 1,5l bottle, for mixing 1:2	D-100-0159
Water hardness test strip	91-78-1

11 Reamer blades




Reamer blade Power Lock Plus (internal thread UNF 3/8" x 24)

For pReam cleaning station

Overview of reamer blades	Part-No.	Part-No.	Part-No.
Inner diameter of the gas nozzle	short	flush	long
16 mm	-	82-8-1-16-F	82-8-1-16-R

Abmessungen	Part-No.					
A	B	C	D	E	F	
16 mm inner diameter						
44	-	59	15.5	-	9	82-8-1-16-F
44	-	62	15.5	-	9	82-8-1-16-R



Reamer blade Power Lock Plus (internal thread M10 x 1)

For eReam 2.0 cleaning station



Overview of reamer blades	Part-No.	Part-No.	Part-No.
Inner diameter of the gas nozzle	short	flush	long
16 mm	-	82-8-2-16-F	82-8-2-16-R

Dimensions	Part-No.					
A	B	C	D	E	F	
16 mm inner diameter						
66	-	81	15.5	-	9	82-8-2-16-F
66	-	84	15.5	-	9	82-8-2-16-R

Please note:

Dimensions in mm.

13 TCP dimensions



Overview of torch necks

HQX dressing	Frontpull 8 – 23° version				Frontpull 8 – 0° version		
	A	B	C	D	A	B	C
Part-No.	(distance in mm)	(TCP length in mm)	(angle in °)	(angle in °)	(distance in mm)	(TCP length in mm)	(angle in °)
58-127-722-350-1	77.0	527.1	45	22	71.3	570.8	22
58-127-722-400-1	96.6	573.1	45	22	71.3	620.8	22
58-127-735-400-1	121.0	561.7	58	35	44.3	619.7	35
58-127-745-350-1	120.7	506.2	68	45	22.9	568.6	45
58-127-745-400-1	140.2	552.2	68	45	22.9	618.6	45
58-427-7345-450-1	163.4	529.9	68	45	-7.07	607.1	45
58-427-7345-567-1	209.1	637.6	68	45	-7.07	724.1	45

13 Checking fixtures

Checking fixtures

To check TCP of torch necks and complete torch.

Checking fixtures are provided for all listed torch necks with Frontpull 8 torch system. Please contact us for detailed information.



Top view checking fixture



Please note:

Further information can be found in our brochure "Checking fixtures" (DOC-0137EN).

13 Torch cleaning stations

eReam 2.0 for
a precise cleaning of
the torch frontend

Pure
Electric.

For further information
please scan this QR code:



Please note:

Further information can be found in our eReam 2.0 brochure (DOC-0205EN).

pReam: pneumatic
cleaning station

Further information can
be found here:



SKS

WELDING SYSTEMS




Contact:
[sales@
de.sks-welding.com](mailto:sales@de.sks-welding.com)

SKS Welding Systems GmbH


Marie-Curie-Str. 14 | 67661 Kaiserslautern | Germany | Phone +49 6301 7986-0

www.sks-welding.com

 /sksweldingsystems

 @sks_welding_systems

 /DesignTechnologyPerformance

 /sks-welding-systems